Imaging on a Budget

A quick survey of DSLR Imaging

By

Richard Jakiel

#### The DSLR vs. the CCD

#### The DSLR..

- Relatively inexpensive
- Fairly large format
- No cooling needed
- Easier to Process
- Very versatile
- Can be used for "normal imaging"

#### A CCD...

- Greater dynamic range
- More sensitive "QE"
- Higher resolution with monochrome CCD
- Narrow Band and filter imaging



#### For long exposure – a different setup

- For Prime Focus and Piggy Back – need a tracking mount. Autoguider controlled the best
- "Live View" or Computer for focusing
- A DSUB controller or remote cable control
- T-ring + adapter (2-inch)
- Power supply (batteries and/or AC adapter)
- Memory cards or large computer HD









Tripod Imaging

### **Tripod Imaging**

- No special setup just camera + lens and tripod
- Usually short exposures (less than 30 seconds)
- Can use stacking to increase signal to noise (s/n)
- Good for conjunctions, the Moon, constellations, Milky Way and other subjects (i.e. satellites)

## 300mm Lunar Images



# Piggy Back Imaging

M11 - 200mm Lens



## Star Clouds around NGC 6520



### M31 and Satellites





Prime Focus Imaging...



M27 - 8-inch f/4


#### So what is Prime Focus Imaging?

- The DSLR is attached directly to the telescope
- Focus is critical. Computer programs can make this easy.
- Need good tracking can be aided with an autoguider



#### Focus – is *critical* for nice images





- Use star clusters and/or areas with a good range of star magnitudes
- "fwhm" or "full width, half max" function is a way to determine the sharpness of the peak = focus!


#### Guiding – Autoguider setup...




- Autoguider = Guide scope plus a Guide Camera, usually mounted "piggyback"
- Guide scope focal length no less than 1/3 the primary scope
- Camera CMOS or CCD, when possible use a CCD as they have lower noise.

#### Choosing a "Guide Program"

- The most "bang for the buck – PhD or "Push here Dummy"
- Able to use most dedicated guide cameras, plus a number of CCD's and even planetary cameras
- Guiding exposures should be >1 second
- Can take 'dark frames' to reduce noise in CMOS cameras




#### Dark Frames and Flat Fields



- Dark frames used to remove thermo noise generated by CMOS and CCD chips. Though DSLRS often have low noise, they are generally NOT cooled.
- Flat Fields correct for vignetting and dirt/imperfections in the imaging train. Can be taken at twilight or other methods. ~ Average of 5 to 10 frames at 20 to 30 K ADU's

### Boosting your contrast – LPS filters





- Imaging from Suburbs deal with a wide variety of light pollution sources
- LPS filters *light pollution suppression filters* can boost contrast (or relative s/n by up to 3x. Works best under moderately polluted skies.
- But even those specifically made for DSLR's and CCD's can shift the color balance needs to adjusted during the processing.

#### Imaging Tips..

- Use "raw mode" instead of .jpg or other compressed formats
- Take a series of *dark frames* to match exposure times and for changes in nightly temperature.
- Flat fields may be necessary if the optics and/or camera chip is dirty and/or unevenly illuminated.
- Try different ISO's other than the highest gain setting.
- Use stacking to reduce noise, boost signal and remove tracking errors.


### Image Gallery – M31 (8-inch f/4)







## Putting the Red Back – The Modified DSLR



• This can be replaced with a clear filter or one that blocks IR/UV without removing the H-alpha signal.












#### High Resolution Imaging of PNe




- Long Focal Length, a large stack of short exposures
- Can use programs like Registax to sharpen/process image
- Doesn't require autoguiding

And now – part II...





Fun with Image Processing!

### Nebulosity – Inexpensive & Easy to Use



O O DSLR Shutter		
DSLR Shutter		
www.Stark-Labs.com		
Exposure control		
# Exposures	20	
Duration	9 0	•
▼ Enable Mirror-lockup		
Delay control		
Sequence start	10	•
Before frame	1	•
After frame	5	10
Start Sequence		
Abort Sequence		
Total Remaining 00:31:59		
90s exposure (1/20)		





# A few more images – M51 (8" f/4)



### M65 and M66



## NGC 4725 (1) and 4718 (r)



